

MATERIAL SAFETY DATA SHEET

JT EATONTM
SINCE 1932

JT EATON FLY TRAPS FOR WINDOWS
Product No. 443

1393 East Highland Road
Twinsburg, OH 44087 • U.S.A.

SECTION 1 • IDENTIFICATION

IDENTITY:

JT EATON FLY TRAP FOR WINDOWS

EPA Registration No. NONE

CHEMICAL FAMILY: Petro Chemical

Marketed by:

J.T. EATON & CO., Inc.

Address: 1393 East Highland Road

Twinsburg, Ohio 44087

Date Prepared: June 15, 2014

HMIS Rating: Health: 1
Flammability: 0
Reactivity: 0
Personal Protection: -
Other:

Emergency Telephone Number: **1-216-421-2116** or

National Pesticide Telecommunications Network at **1-800-858-7378**

Telephone Number for Information:

9 AM to 5 PM EST - **1-216-421-2116**

SECTION 2 HAZARDOUS INGREDIENTS

HAZARDOUS COMPONENTS	CAS NUMBER	PEL	STEL	<-OSHA LIMITS -> CEILING	ACGIH TLV	OPTIONAL %
NONE		N/A	N/A	N/A	N/A	N/A

This Material Safety Data sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Material Information System (WHMIS). Unlisted ingredients are not "hazardous" per the OSHA standard and/or are not found on the WHMIS ingredient disclosure list.

SECTION 3 • PHYSICAL / CHEMICAL DATA

BOILING POINT: (C): N/A

VAPOR PRESSURE: (mm hg): N/A

VAPOR DENSITY: (AIR = 1): N/A

SOLUBILITY IN H₂O: Insoluble

SPECIFIC GRAVITY (H₂O = 1): 0.912

BULK DENSITY: 8.5 lbs. gallon

MELTING POINT: N/A

EVAPORATION RATE (Butyl Acetate = 1): N/A

% VOLATILE: N/A

APPEARANCE / ODOR: Light yellow transparent solid,
negligible odor.

SECTION 4 • FIRE & EXPLOSION HAZARD DATA

FLASH POINT (Method Used) - Greater than 400°F:
Seta-Flash Closed Tester

FLAMMABLE LIMITS: Insignificant LEL: N/A UEL: N/A

EXTINGUISHING MEDIA: CO₂, Dry Chemical, Foam

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should be equipped with self-contained breathing apparatus to protect against potentially toxic and irritating fumes.

UNUSUAL FIRE & EXPLOSION HAZARDS: Combustion may release noxious or toxic vapors.

SECTION 5 • REACTIVITY DATA

CHEMICAL STABILITY: Stable.

CONDITIONS TO AVOID: Not applicable.

INCOMPATIBLE MATERIALS: None known.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS (*from burning, heating, or reaction with other materials*):
Carbon Monoxide, Carbon Dioxide, Unknown Hydrocarbons.

SECTION 6 • HEALTH HAZARD DATA

ROUTES OF ENTRY: INHALATION? SKIN? INGESTION?
YES YES YES

HEALTH HAZARDS (ACUTE and CHRONIC): Negligible, below 250°F
other than thermal hazards above 120°F.

CARCINOGENICITY: **None known.**

NTP? IARC MONOGRAPH? OSHA REGULATED?
NO NO NO

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Ingestion may cause slight diarrhea. Contact with open wounds not recommended.

EMERGENCY AND FIRST AID PROCEDURES:

None required. Sticky adhesive may be removed with vegetable oil.

SECTION 7 • PRECAUTIONS FOR SAFE HANDLING

IN CASE MATERIAL IS RELEASED OR SPILLED: At temperatures below 120°F pick up the products. Above 120°F use thermal protection when picking up product.

WASTE DISPOSAL METHOD: In accordance with existing Federal, State and Local environmental regulations.
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in cool dry area.

SECTION 8 • CONTROL MEASURES

RESPIRATORY PROTECTION: None below 250°F
VENTILATION:

LOCAL EXHAUST: None below 250°F
SPECIAL: N/A
MECHANICAL EXHAUST: None below 250°F

EYE PROTECTION: N/A
WORK / HYGIENIC PRACTICES: Standard practices.

PROTECTIVE GLOVES: When above 120°F

SECTION 9 • CALIFORNIA ADDENDUM (PROPOSITION 65) SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986

The following specific warnings are hereby given relative to substances that the State of California has identified as carcinogens and/or reproductive hazards under Proposition 65:

WARNING: None WARNING: None

SECTION 10 • SARA TITLE III HAZARD CATEGORY

For Reporting Under Sections 311 & 312

Immediate - NO Delayed - NO Fire - NO Reactive - NO Sudden Release of Pressure - NO

SARA Title III (40CFR311/312) Hazard category: Not applicable.

SARA Title III Section 313 Toxic chemical substances present at above de-minimus concentrations: None

SECTION 11 • SHIPPING INFORMATION

HAZARD CLASS: D.O.T. Placarding Not Required

BILL OF LADING DESCRIPTION: Adhesive, NOI

UN IDENTIFICATION NUMBER: N/A

PACKING GROUP: N/A

Manufacturer makes no warranty, express or implied, other than indicated on Label and MSDS. Customer assumes all risk of use and/or handling of this material when such use and / or handling is contrary to Label and MSDS.

All information contained in this Material Safety Data Sheet is furnished free of charge and is intended for your evaluation. In our opinion the information is, as of the date of this Material Safety Data Sheet, reliable, however, it is your responsibility to determine the suitability of the information for your use. You are advised not to construe the information as absolutely complete since additional information may be necessary or desirable when particular, exceptional or variable conditions or circumstances exist or because of applicable laws or government regulations. Therefore, you should use this information only as a supplement to other information gathered by you and you must make independent determinations of the suitability and completeness of the information from all sources to assure both proper use of the material described herein and the safety and health of employees. Accordingly, no guarantee expressed or implied is made by J.T. Eaton & Co., Inc. as to the results to be obtained based upon your use of the information nor does J.T. Eaton & Co., Inc. assume any liability arising out of your use of the information.

JT EATON FLY TRAP FOR WINDOWS

EPA Registration No. **NONE**

Page 2