

MATERIAL SAFETY DATA SHEET

JT EATON TOP COAT PROTECTOR

JT EATONTM

1393 East Highland Road
Twinsburg, OH 44087 • U.S.A.

SECTION 1 • IDENTIFICATION

IDENTITY:

JT EATON TOP COAT PROTECTOR

EPA Registration No. **NONE**

ACTIVE INGREDIENT CHEMICAL NAME: MIXTURE

CHEMICAL FAMILY:

Manufacturer's Name:

J.T.EATON & CO., INC.

1393 East Highland Road

Twinsburg, Ohio 44087

Date Prepared: June 15, 2014

HMIS Rating: Health: 2
Flammability: 4
Reactivity: 0
Personal Protection: 0

Emergency Telephone Number: **1-800-664-9042** or

National Pesticide Telecommunications Network at **1-800-858-7378**

Telephone Number for Information:

9 AM to 5 PM EST - 330-425-7801

SECTION 2 HAZARDOUS INGREDIENTS

HAZARDOUS COMPONENTS	CAS NUMBER	PEL	STEL	<- OSHA LIMITS ->		OPTIONAL
				CEILING	ACGIH TLV	%
Propane	74-98-6	1000	N/A	1000	N/A	15
Butane	106-97-8	800	N/A	800	800	15
Lt. Aliphatic Hydrocarbon Solvent	64742-89-8	100	N/A	100	100	6
Ethylbenzene	100-41-4	100	N/A	100	100	4
Medium Aromatic Hydrocarbons	64742-94-5	Not Established	N/E	N/E	N/E	2
Xylene	1330-20-7	100	N/A	100	100	23
Acetone	67-64-1	750	N/A	750	750	26

SECTION 3 • PHYSICAL / CHEMICAL DATA

BOILING POINT: (F): <0 - 415° F

VAPOR PRESSURE: (mm hg): 760

VAPOR DENSITY (AIR = 1): Heavier than air.

SOLUBILITY IN H₂O: N/A

APPEARANCE / ODOR: Clear. Sweet solvent odor.

BULK DENSITY: 8.5 lb. per gallon

MELTING POINT: N/A

EVAPORATION RATE (Butyl Acetate = 1): Faster than ether.

% VOLATILE: 95%

SPECIFIC GRAVITY (H₂O = 1): 0.72

SECTION 4 • FIRE & EXPLOSION HAZARD DATA

FLASH POINT (Method Used) - <0° F

FLAMMABLE LIMITS: Extremely Flammable Flash below 21°F

LEL: 0.8 UEL: 12.8

EXTINGUISHING MEDIA: Foam, Carbon Dioxide (CO₂), dry chemical.

UNUSUAL FIRE & EXPLOSION HAZARDS: Isolate from heat, electrical equipment, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES: Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible auto-ignition or explosion when exposed to extreme heat.

SECTION 5 • REACTIVITY DATA

CHEMICAL STABILITY: Stable.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Dioxide, Carbon Monoxide.

INCOMPATIBLE MATERIALS: None known.

HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS TO AVOID: None known.