

MATERIAL SAFETY DATA SHEET

JT EATON PROFESSIONAL STRENGTH ROACH GLUE BOARDS

JT EATONTM
SINCE 1932

1393 East Highland Road
Twinsburg, OH 44087 • U.S.A.

SECTION 1 • IDENTIFICATION

IDENTITY:

JT EATON PROFESSIONAL STRENGTH ROACH GLUE BOARDS

EPA Registration No. **NONE**

ACTIVE INGREDIENT CHEMICAL NAME: **NONE**

CHEMICAL FAMILY: Hot Melt Adhesive/Thermoplastic

Manufacturer's Name:

J.T.EATON & CO., INC.

1393 East Highland Road

Twinsburg, Ohio 44087

Prepared by: Bart Baker Date Prepared: June 18, 2010

HMIS Rating: Health: 1
Flammability: 0
Reactivity: 0
Personal Protection: -
Other:

Emergency Telephone Number: **1-800-664-9042** or

National Pesticide Telecommunications Network at **1-800-858-7378**

Telephone Number for Information:

9 AM to 5 PM EST - 330-425-7801

SECTION 2 HAZARDOUS INGREDIENTS

HAZARDOUS COMPONENTS	CAS NUMBER	PEL	STEL	<- OSHA LIMITS ->		OPTIONAL
				CEILING	ACGIH TLV	%
Nonhazardous according to 29 CFR 1910-1200		N/A	N/A	N/A	N/A	N/A

This Material Safety Data sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Material Information System (WHMIS). Unlisted ingredients are not "hazardous" per the OSHA standard and/or are not found on the WHMIS ingredient disclosure list.

SECTION 3 • PHYSICAL / CHEMICAL DATA

BOILING POINT: (F): N/A

VAPOR PRESSURE: (mm hg): Negligible at Ambient.

VAPOR DENSITY: (AIR = 1): N/A

SOLUBILITY IN H₂O: Not soluble.

SPECIFIC GRAVITY (H₂O = 1): 0.98

BULK DENSITY: N/A

MELTING POINT: N/A

EVAPORATION RATE (Butyl Acetate = 1): N/A

% VOLATILE: Zero (0° F) at room temp., <1.0% when heated.

APPEARANCE / ODOR: Off-white to tan colored solid.
Characteristic Odor: Resinous odor.

SECTION 4 • FIRE & EXPLOSION HAZARD DATA

FLASH POINT (Method Used) - Higher than 400° F (Cleveland Open Cup)

FLAMMABLE LIMITS: N/D LEL: N/A UEL: N/D

EXTINGUISHING MEDIA: In case of fire use: Water Spray, Foam,
Dry Chemical.

SPECIAL FIRE FIGHTING PROCEDURES: Fire fighters should wear self contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

UNUSUAL FIRE & EXPLOSION HAZARDS: Decomposition may produce hazardous chemicals such as CO, NO and other unknown hazards and smoke smoke material is flammable.

SECTION 5 • REACTIVITY DATA

CHEMICAL STABILITY: Stable.

CONDITIONS TO AVOID: Oxidizing materials may cause reaction..

INCOMPATIBLE MATERIALS: N/A

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS (from burning, heating, or reaction with other materials):
Oxides of Carbon and smoke.

SECTION 6 • HEALTH HAZARD DATA

ROUTES OF ENTRY: **INHALATION?** **SKIN?** **INGESTION?**

In Molten State In Molten State Not Likely

HEALTH HAZARDS (ACUTE and CHRONIC): Molten adhesive may cause burns to skin. Excessive heating (>450° F) may produce vapors causing irritation of mucous membrane and respiratory tract.

CARCINOGENICITY: **None known.**

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None known.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Immediately flush eyes with water for at least 15 minutes. Call a physician.

SKIN: If burn is caused by skin contact with molten adhesive, cool area with water. See physician for treatment of thermal burn.

INHALATION: Move patient to fresh air.

NTP?

NO

IARC MONOGRAPH?

NO

OSHA REGULATED?

NO

SECTION 7 • PRECAUTIONS FOR SAFE HANDLING

IN CASE MATERIAL IS RELEASED OR SPILLED: Sweep up and place in container for recycle or disposal. If molten adhesive is spilled, let it cool to solid state before removal.

WASTE DISPOSAL METHOD: Consult expert to comply with Local, State and Federal Regulations. Dispose as solid waste.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep in dry place. Keep containers closed. Avoid contamination with dust, water or oxidizing agents.

SECTION 8 • CONTROL MEASURES

RESPIRATORY PROTECTION: Generally not needed.
VENTILATION:

LOCAL EXHAUST: Generally not needed.
SPECIAL: NO
MECHANICAL EXHAUST: NO
OTHER: NO

EYE PROTECTION: Splash proof eye goggles. Where contact may occur with hot materials, wear a face shield.

WORK / HYGIENIC PRACTICES: Provide readily accessible eye wash stations. Wash promptly if skin becomes contaminated. Remove from skin with vegetable oil.

PROTECTIVE GLOVES: Rubber gloves, latex rubber. Contact with hot materials, wear thermal resistant gloves and arm protection.

SECTION 9 • CALIFORNIA ADDENDUM

(PROPOSITION 65) SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986

The following specific warnings are hereby given relative to substances that the State of California has identified as carcinogens and/or reproductive hazards under Proposition 65:

WARNING: None

WARNING: None

SECTION 10 • SARA TITLE III HAZARD CATEGORY

For Reporting Under Sections 311 & 312

Immediate - NO Delayed - NO Fire - NO Reactive - NO Sudden Release of Pressure - NO

SARA Title III (40CFR311/312) Hazard category: Not applicable.

SARA Title III Section 313 Toxic chemical substances present at above de-minimus concentrations: None

SECTION 11 • SHIPPING INFORMATION

HAZARD CLASS: D.O.T. Placarding Not Required

BILL OF LADING DESCRIPTION: Adhesive Glue Traps Item 187120
Sub Class 70 Density 16 lbs/CU Ft.
Insecticides Item 102120 Class 60

Manufacturer makes no warranty, express or implied, other than indicated on Label and MSDS. Customer assumes all risk of use and/or handling of this material when such use and / or handling is contrary to Label and MSDS.

All information contained in this Material Safety Data Sheet is furnished free of charge and is intended for your evaluation. In our opinion the information is, as of the date of this Material Safety Data Sheet, reliable, however, it is your responsibility to determine the suitability of the information for your use. You are advised not to construe the information as absolutely complete since additional information may be necessary or desirable when particular, exceptional or variable conditions or circumstances exist or because of applicable laws or government regulations. Therefore, you should use this information only as a supplement to other information gathered by you and you must make independent determinations of the suitability and completeness of the information from all sources to assure both proper use of the material described herein and the safety and health of employees. Accordingly, no guarantee expressed or implied is made by J.T. Eaton & Co., Inc. as to the results to be obtained based upon your use of the information nor does J.T. Eaton & Co., Inc. assume any liability arising out of your use of the information.

JT EATON PROFESSIONAL STRENGTH ROACH GLUE BOARDS

EPA Registration No. NONE

Page 2